

PROPELLERS

WOT RPM: 5600-6200 * Recommended Transom Height 20" * Right Hand Rotation * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.00"	25	3	Steel	2000-2300	Up to 19'	69-78	Fury	48-8M0125097	N/A
14.5"	25	4	Steel	2000-2300	Up to 19'	69-78	Fury 4	48-8M0125101	N/A
14.62"	25	3	Steel	2000-2300	Up to 19'	69-78	Tempest Plus**	48-825866A47	N/A
13.75"	25	4	Steel	2000-2300	Up to 19'	69-78	Trophy Plus**	48-825942A47	N/A
14.00"	24	3	Steel	2100-2400	18-20'	66-75	Fury	48-8M0125096	N/A
14.5"	24	4	Steel	2100-2400	18-20'	66-75	Fury 4	48-8M0125100	N/A
15.5"	24	4	Steel	2100-2400	18-20'	66-75	Bravo 1**	48-831912A45	N/A
14.62"	24	3	Steel	2100-2400	18-20'	66-75	Tempest Plus**	48-825872A47	N/A
13.75"	24	4	Steel	2100-2400	18-20'	66-75	Trophy Plus**	48-825940A47	N/A
14.00"	23	3	Steel	2200-2500	19-21'	63-71	Fury	48-8M0125095	N/A
14.5"	23	4	Steel	2200-2500	19-21'	63-71	Fury 4	48-8M0125099	N/A
14.62"	23	3	Steel	2200-2500	19-21'	63-71	Tempest Plus**	48-825864A47	N/A
13.75"	23	4	Steel	2200-2500	19-21'	63-71	Trophy Plus**	48-825938A47	N/A
15.5"	22	4	Steel	2300-2700	19-22'	60-68	Bravo 1**	48-831910A45	N/A
14.62"	21	3	Steel	2500-3000	20-22'	57-64	Tempest Plus**	48-825862A47	N/A
13.75"	21	4	Steel	2500-2800	20-22'	57-64	Trophy Plus**	48-825938A47	N/A

Mercury 4.6 L V8 225 HP Pro XS Torque Master

Serial Number: 2B529482 & Up

PROPELLERS

WOT RPM: 5600-6200 * Recommended Transom Height 20" * Right Hand Rotation * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.00"	26	3	Steel	2100-2400	Up to 19'	72-82	Fury	48-8M0125098	N/A
14.5"	26	4	Steel	2100-2400	Up to 19'	72-82	Fury 4	48-8M0125102	N/A
15.5"	26	4	Steel	2100-2400	Up to 19'	72-82	Bravo 1**	48-831914A45	N/A
14.62"	26	3	Steel	2100-2400	Up to 19'	72-82	Tempest Plus**	48-825874A47	N/A
14.00"	25	3	Steel	2200-2500	18-20'	69-78	Fury	48-8M0125097	N/A
14.5"	25	4	Steel	2200-2500	18-20'	69-78	Fury 4	48-8M0125101	N/A
14.62"	25	3	Steel	2200-2500	18-20'	69-78	Tempest Plus**	48-825866A47	N/A
14.00"	24	3	Steel	2300-2700	19-21'	66-75	Fury	48-8M0125096	N/A
14.5"	24	4	Steel	2300-2700	19-21'	66-75	Fury 4	48-8M0125100	N/A
15.5"	24	4	Steel	2300-2700	19-21'	66-75	Bravo 1**	48-831912A45	N/A
14.62"	24	3	Steel	2300-2700	19-21'	66-75	Tempest Plus**	48-825872A47	N/A
14.00"	23	3	Steel	2500-2800	19-21'	63-71	Fury	48-8M0125095	N/A
14.5"	23	4	Steel	2500-2800	19-21'	63-71	Fury 4	48-8M0125099	N/A
14.62"	23	3	Steel	2500-2800	19-21'	63-71	Tempest Plus**	48-825864A47	N/A
15.5"	22	4	Steel	2600-3000	19-22'	60-68	Bravo 1**	48-831910A45	N/A
14.62"	21	3	Steel	2800-3200	20-22'	57-64	Tempest Plus**	48-825862A47	N/A

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit



PROPELLERS

WOT RPM: 5600-6200 * Recommended Transom Height 20" * Right Hand Rotation * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.00"	27	3	Steel	2200-2600	Up to 19'	75-85	Fury**	48-8M8023180	N/A
14.62"	27	3	Steel	2200-2600	Up to 19'	75-85	Tempest Plus**	48-825868A47	N/A
14.00"	26	3	Steel	2300-2700	18-20'	72-82	Fury	48-8M0125098	N/A
14.5"	26	4	Steel	2300-2700	18-20'	72-82	Fury 4	48-8M0125102	N/A
15.5"	26	4	Steel	2300-2700	18-20'	72-82	Bravo 1**	48-831914A45	N/A
14.62"	26	3	Steel	2300-2700	18-20'	72-82	Tempest Plus**	48-825874A47	N/A
14.00"	25	3	Steel	2500-2800	18-20'	69-78	Fury	48-8M0125097	N/A
14.5"	25	4	Steel	2500-2800	18-20'	69-78	Fury 4	48-8M0125101	N/A
14.62"	25	3	Steel	2500-2800	18-20'	69-78	Tempest Plus**	48-825866A47	N/A
14.00"	24	3	Steel	2600-3000	19-21'	66-75	Fury	48-8M0125096	N/A
14.5"	24	4	Steel	2600-3000	19-21'	66-75	Fury 4	48-8M0125100	N/A
15.5"	24	4	Steel	2600-3000	19-21'	66-75	Bravo 1**	48-831912A45	N/A
14.62"	24	3	Steel	2600-3000	19-21'	66-75	Tempest Plus**	48-825872A47	N/A
14.00"	23	3	Steel	2700-3100	19-21'	63-71	Fury	48-8M0125095	N/A
14.5"	23	4	Steel	2700-3100	19-21'	63-71	Fury 4	48-8M0125099	N/A
14.62"	23	3	Steel	2700-3100	19-21'	63-71	Tempest Plus**	48-825864A47	N/A
15.5"	22	4	Steel	2900-3300	20-22'	60-68	Bravo 1**	48-831910A45	N/A
14.62"	21	3	Steel	3100-3500	20-22'	57-64	Tempest Plus**	48-825862A47	N/A

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit

Mercury 4.6 L V8 300 HP Pro XS Torque Master

Serial Number: 2B529482 & Up

PROPELLERS

WOT RPM: 5600-6200 * Recommended Transom Height 20" * Right Hand Rotation * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.00"	27	3	Steel	2700-3100	18-21'	75-85	Fury**	48-8M8023180	N/A
14.62"	27	3	Steel	2700-3100	18-21'	75-85	Tempest Plus**	48-825868A47	N/A
14.00"	26	3	Steel	2800-3200	19-21'	72-82	Fury	48-8M0125098	N/A
14.5"	26	4	Steel	2800-3200	19-21'	72-82	Fury 4	48-8M0125102	N/A
15.5"	26	4	Steel	2800-3200	19-21'	72-82	Bravo 1**	48-831914A45	N/A
14.62"	26	3	Steel	2800-3200	19-21'	72-82	Tempest Plus**	48-825874A47	N/A
14.00"	25	3	Steel	3000-3400	19-21'	69-78	Fury	48-8M0125097	N/A
14.5"	25	4	Steel	3000-3400	19-21'	69-78	Fury 4	48-8M0125101	N/A
14.62"	25	3	Steel	3000-3400	19-21'	69-78	Tempest Plus**	48-825866A47	N/A
14.00"	24	3	Steel	3100-3600	20-22'	66-75	Fury	48-8M0125096	N/A
14.5"	24	4	Steel	3100-3600	20-22'	66-75	Fury 4	48-8M0125100	N/A
15.5"	24	4	Steel	3100-3600	20-22'	66-75	Bravo 1**	48-831912A45	N/A
14.62"	24	3	Steel	3100-3600	20-22'	66-75	Tempest Plus**	48-825872A47	N/A
14.00"	23	3	Steel	3300-3800	20-22'	63-71	Fury	48-8M0125095	N/A
14.5"	23	4	Steel	3300-3800	20-22'	63-71	Fury 4	48-8M0125099	N/A
14.62"	23	3	Steel	2300-2500	20-22'	63-71	Tempest Plus**	48-825864A47	N/A
15.5"	22	4	Steel	3500-4000	21-23'	60-68	Bravo 1**	48-831910A45	N/A
14.62"	21	3	Steel	3700-4200	21-23'	57-64	Tempest Plus**	48-825862A47	N/A

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit



PROPELLERS

WOT RPM: 5600-6200 * Recommended Transom Height 25" * Right Hand Rotation * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.00"	24	3	Steel	2100-2400	17-19'	66-75	Fury	48-8M0125096	N/A
14.5"	24	4	Steel	2100-2400	17-19'	66-75	Fury 4	48-8M0125100	N/A
14.62"	24	3	Steel	2100-2400	17-19'	66-75	Tempest Plus**	48-825872A47	N/A
13.75"	24	4	Steel	2100-2400	17-19'	66-75	Trophy Plus**	48-825940A47	N/A
14.00"	23	3	Steel	2200-2500	18-20'	63-71	Fury	48-8M0125095	N/A
14.5"	23	4	Steel	2200-2500	18-20'	63-71	Fury 4	48-8M0125099	N/A
14.62"	23	3	Steel	2200-2500	18-20'	63-71	Tempest Plus**	48-825864A47	N/A
13.75"	23	4	Steel	2200-2500	18-20'	63-71	Trophy Plus**	48-825938A47	N/A
13.5"	22	3	Steel	2300-2700	18-20'	60-68	Enertia**	48-899202A46	N/A
14.62"	21	3	Steel	2500-2800	19-21'	57-64	Tempest Plus**	48-825862A47	N/A
13.8"	21	3	Steel	2500-2800	19-21'	57-64	Enertia**	48-899002A46	N/A
13.25"	21	5	Steel	2500-2800	19-21'	57-64	HighFive**	48-815760A46	N/A
14.75"	21	3	Steel	2500-2800	19-21'	57-64	Mirage Plus**	48-13702A46	N/A
13.75"	21	4	Steel	2500-2800	19-21'	57-64	Trophy Plus**	48-825934A47	N/A
13.8"	20	3	Steel	2600-3000	19-22'	54-61	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	2600-3000	19-22'	54-61	Enertia ECO	48-8M0127047	N/A
14.62"	19	3	Steel	2800-3200	20-22'	51-58	Tempest Plus**	48-825860A47	N/A
14.0"	19	3	Steel	2800-3200	20-22'	51-58	Enertia**	48-898998A46	N/A
13.25"	19	5	Steel	2800-3200	20-22'	51-58	HighFive**	48-815758A46	N/A
14.62"	19	4	Steel	2800-3200	20-22'	51-58	Revolution 4	48-8M0127031	N/A
16.00"	19	3	Steel	2800-3200	20-22'	51-58	Enertia ECO	48-8M0127045	N/A
15.25"	19	3	Steel	2800-3200	20-22'	51-58	Mirage Plus**	48-13700A46	N/A
14.2"	18	3	Steel	2900-3400	20-22'	48-55	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	2900-3400	20-22'	48-55	Enertia ECO	48-8M0127043	N/A
14.62"	18	4	Steel	2900-3400	20-22'	48-55	Revolution 4	48-8M0137924	N/A
14.5"	17	3	Steel	3200-3800	21-23'	44-51	Enertia**	48-898994A46	N/A
16.00"	17	3	Steel	3200-3800	21-23'	44-51	Enertia ECO	48-8M0127041	N/A
15.5"	17	3	Steel	3200-3800	21-23'	44-51	Mirage Plus**	48-18278A46	N/A
13.5"	17	5	Steel	3200-3800	21-23'	44-51	HighFive**	48-821154A46	N/A
14.62"	17	4	Steel	3200-3800	21-23'	44-51	Revolution 4	48-8M0127029	N/A
14.7"	16	3	Steel	3400-4100	21-23'	41-48	Enertia**	48-898992A46	N/A

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit



Revolution 4

Aggressive four-blade design provides outstanding holding, hole shot and improved midrange performance.



SpitFire X7

Superior acceleration generated through a small diameter design. Ultimate top speed and holding through aggressive cup.

PROPELLERS

WOT RPM: 5600-6200 * Recommended Transom Height 25" * Right Hand Rotation * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.00"	25	3	Steel	2200-2500	18-20'	69-78	Fury	48-8M0125097	N/A
14.5"	25	4	Steel	2200-2500	18-20'	69-78	Fury 4	48-8M0125101	N/A
14.62"	25	3	Steel	2200-2500	18-20'	69-78	Tempest Plus**	48-825866A47	N/A
14.00"	24	3	Steel	2300-2700	18-20'	66-75	Fury	48-8M0125096	N/A
14.5"	24	4	Steel	2300-2700	18-20'	66-75	Fury 4	48-8M0125100	N/A
14.62"	24	3	Steel	2300-2700	18-20'	66-75	Tempest Plus**	48-825872A47	N/A
14.00"	23	3	Steel	2500-2800	19-21'	63-71	Fury	48-8M0125095	N/A
14.5"	23	4	Steel	2500-2800	19-21'	63-71	Fury 4	48-8M0125099	N/A
14.62"	23	3	Steel	2500-2800	19-21'	63-71	Tempest Plus**	48-825864A47	N/A
13.5"	22	3	Steel	2600-3000	19-21'	60-68	Enertia**	48-899202A46	N/A
14.62"	21	3	Steel	2800-3200	19-22'	57-64	Tempest Plus**	48-825862A47	N/A
13.8"	21	3	Steel	2800-3200	19-22'	57-64	Enertia**	48-899002A46	N/A
13.25"	21	5	Steel	2800-3200	19-22'	57-64	HighFive**	48-815760A46	N/A
14.75"	21	3	Steel	2800-3200	19-22'	57-64	Mirage Plus**	48-13702A46	N/A
13.8"	20	3	Steel	2900-3400	20-22'	54-61	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	2900-3400	20-22'	54-61	Enertia ECO	48-8M0127047	N/A
14.62"	20	4	Steel	2900-3400	20-22'	54-61	Revolution 4	48-8M0127033	N/A
14.62"	19	3	Steel	3100-3600	20-22'	51-58	Tempest Plus**	48-825860A47	N/A
14.0"	19	3	Steel	3100-3600	20-22'	51-58	Enertia**	48-898998A46	N/A
13.25"	19	5	Steel	3100-3600	20-22'	51-58	HighFive**	48-815758A46	N/A
14.62"	19	4	Steel	3100-3600	20-22'	51-58	Revolution 4	48-8M0127031	N/A
16.00"	19	3	Steel	3100-3600	20-22'	51-58	Enertia ECO	48-8M0127045	N/A
15.25"	19	3	Steel	3100-3600	20-22'	51-58	Mirage Plus**	48-13700A46	N/A
14.2"	18	3	Steel	3300-3800	21-23'	48-55	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	3300-3800	21-23'	48-55	Enertia ECO	48-8M0127043	N/A
14.62"	18	4	Steel	3300-3800	21-23'	48-55	Revolution 4	48-8M0137924	N/A
14.5"	17	3	Steel	3600-4200	22-24'	44-51	Enertia**	48-898994A46	N/A
16.00"	17	3	Steel	3600-4200	22-24'	44-51	Enertia ECO	48-8M0127041	N/A
15.5"	17	3	Steel	3600-4200	22-24'	44-51	Mirage Plus**	48-18278A46	N/A
13.5"	17	5	Steel	3600-4200	22-24'	44-51	HighFive**	48-821154A46	N/A
14.62"	17	4	Steel	3600-4200	22-24'	44-51	Revolution 4	48-8M0127029	N/A

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit



Enertia ECO

Designed for heavy, high-horsepower boats where fuel economy at cruise is top priority.



Fury

Mercury's revolutionary tournament bass propeller.

Designed for class-leading performance for all bass, bay and flats boats running 200hp and above engines.

PROPELLERS

WOT RPM: 5600-6200 * Recommended Transom Height 25" * Right Hand Rotation * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.00"	26	3	Steel	2300-2700	18-20'	72-82	Fury	48-8M0125098	N/A
14.5"	26	4	Steel	2300-2700	18-20'	72-82	Fury 4	48-8M0125102	N/A
14.62"	26	3	Steel	2300-2700	18-20'	72-82	Tempest Plus**	48-825874A47	N/A
14.00"	25	3	Steel	2500-2800	18-21'	69-78	Fury	48-8M0125097	N/A
14.5"	25	4	Steel	2500-2800	18-21'	69-78	Fury 4	48-8M0125101	N/A
14.62"	25	3	Steel	2500-2800	18-21'	69-78	Tempest Plus**	48-825866A47	N/A
14.62"	25	4	Steel	2500-2800	18-21'	69-78	Revolution 4	48-8M0127039	N/A
14.00"	24	3	Steel	2600-3000	19-21'	66-75	Fury	48-8M0125096	N/A
14.5"	24	4	Steel	2600-3000	19-21'	66-75	Fury 4	48-8M0125100	N/A
14.62"	24	3	Steel	2600-3000	19-21'	66-75	Tempest Plus**	48-825872A47	N/A
14.00"	23	3	Steel	2700-3100	19-22'	63-71	Fury	48-8M0125095	N/A
14.5"	23	4	Steel	2700-3100	19-22'	63-71	Fury 4	48-8M0125099	N/A
14.62"	23	3	Steel	2700-3100	19-22'	63-71	Tempest Plus**	48-825864A47	N/A
14.62"	23	4	Steel	2700-3100	19-22'	63-71	Revolution 4	48-8M0127037	N/A
16.0"	23	3	Steel	2700-3100	19-22'	63-71	Enertia ECO	48-8M0127053	N/A
13.5"	22	3	Steel	2900-3300	20-22'	60-68	Enertia**	48-899202A46	N/A
16.00"	22	3	Steel	2900-3300	20-22'	60-68	Enertia ECO	48-8M0127051	N/A
14.62"	21	3	Steel	3100-3500	20-23'	57-64	Tempest Plus**	48-825862A47	N/A
13.8"	21	3	Steel	3100-3500	20-23'	57-64	Enertia**	48-899002A46	N/A
16.00"	21	3	Steel	3100-3500	20-23'	57-64	Enertia ECO	48-8M0127049	N/A
14.62"	21	4	Steel	3100-3500	20-23'	57-64	Revolution 4	48-8M0127035	N/A
14.75"	21	3	Steel	3100-3500	20-23'	57-64	Mirage Plus**	48-13702A46	N/A
13.8"	20	3	Steel	3300-3700	20-23'	54-61	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	3300-3700	20-23'	54-61	Enertia ECO	48-8M0127047	N/A
14.62"	20	4	Steel	3300-3700	20-23'	54-61	Revolution 4	48-8M0127033	N/A
14.62"	19	3	Steel	3400-4000	21-23'	51-58	Tempest Plus**	48-825860A47	N/A
14.0"	19	3	Steel	3400-4000	21-23'	51-58	Enertia**	48-898998A46	N/A
14.62"	19	4	Steel	3400-4000	21-23'	51-58	Revolution 4	48-8M0127031	N/A
16.00"	19	3	Steel	3400-4000	21-23'	51-58	Enertia ECO	48-8M0127045	N/A
15.25"	19	3	Steel	3400-4000	21-23'	51-58	Mirage Plus**	48-13700A46	N/A
14.2"	18	3	Steel	3700-4300	21-23'	48-55	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	3700-4300	21-23'	48-55	Enertia ECO	48-8M0127043	N/A
14.62"	18	4	Steel	3700-4300	21-23'	48-55	Revolution 4	48-8M0137924	N/A
14.5"	17	3	Steel	4000-4700	22-24'	44-51	Enertia**	48-898994A46	N/A
16.00"	17	3	Steel	4000-4700	22-24'	44-51	Enertia ECO	48-8M0127041	N/A
15.5"	17	3	Steel	4000-4700	22-24'	44-51	Mirage Plus**	48-18278A46	N/A
14.62"	17	4	Steel	4000-4700	22-24'	44-51	Revolution 4	48-8M0127029	N/A

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit

PROPELLERS

WOT RPM: 5600-6200 * Recommended Transom Height 25" * Right Hand Rotation (Left Hand Available) * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.00"	26	3	Steel	2800-3200	18-21'	72-82	Fury	48-8M0125098	N/A
14.5"	26	4	Steel	2800-3200	18-21'	72-82	Fury 4	48-8M0125102	N/A
14.62"	26	3	Steel	2800-3200	18-21'	72-82	Tempest Plus**	48-825874A47	N/A
14.00"	25	3	Steel	3000-3400	19-21'	69-78	Fury	48-8M0125097	N/A
14.5"	25	4	Steel	3000-3400	19-21'	69-78	Fury 4	48-8M0125101	N/A
14.62"	25	3	Steel	3000-3400	19-21'	69-78	Tempest Plus**	48-825866A47	N/A
14.62"	25	4	Steel	3000-3400	19-21'	69-78	Revolution 4	48-8M0127039	48-8M0127038
14.00"	24	3	Steel	3100-3600	20-22'	66-75	Fury	48-8M0125096	N/A
14.5"	24	4	Steel	3100-3600	20-22'	66-75	Fury 4	48-8M0125100	N/A
14.62"	24	3	Steel	3100-3600	20-22'	66-75	Tempest Plus**	48-825872A47	N/A
14.00"	23	3	Steel	3300-3800	20-22'	63-71	Fury	48-8M0125095	N/A
14.5"	23	4	Steel	3300-3800	20-22'	63-71	Fury 4	48-8M0125099	N/A
14.62"	23	3	Steel	3300-3800	20-22'	63-71	Tempest Plus**	48-825864A47	N/A
14.62"	23	4	Steel	3300-3800	20-22'	63-71	Revolution 4	48-8M0127037	48-8M0127036
16.0"	23	3	Steel	3300-3800	20-22'	63-71	Enertia ECO	48-8M0127053	48-8M0127052
13.5"	22	3	Steel	3500-4000	21-23'	60-68	Enertia**	48-899202A46	N/A
16.00"	22	3	Steel	3500-4000	21-23'	60-68	Enertia ECO	48-8M0127051	48-8M0127050
14.62"	21	3	Steel	3700-4200	21-23'	57-64	Tempest Plus**	48-825862A47	N/A
13.8"	21	3	Steel	3700-4200	21-23'	57-64	Enertia**	48-899002A46	48-899003A46
16.00"	21	3	Steel	3700-4200	21-23'	57-64	Enertia ECO	48-8M0127049	48-8M0127048
14.62"	21	4	Steel	3700-4200	21-23'	57-64	Revolution 4	48-8M0127035	48-8M0127034
14.75"	21	3	Steel	3700-4200	21-23'	57-64	Mirage Plus**	48-13702A46	48-13703A46
13.8"	20	3	Steel	3900-4500	22-24'	54-61	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	3900-4500	22-24'	54-61	Enertia ECO	48-8M0127047	48-8M0127046
14.62"	20	4	Steel	3900-4500	22-24'	54-61	Revolution 4	48-8M0127033	48-8M0127032
14.62"	19	3	Steel	4100-4800	22-24'	51-58	Tempest Plus**	48-825860A47	N/A
14.0"	19	3	Steel	4100-4800	22-24'	51-58	Enertia**	48-898998A46	48-898999A46
14.62"	19	4	Steel	4100-4800	22-24'	51-58	Revolution 4	48-8M0127031	48-8M0127030
16.00"	19	3	Steel	4100-4800	22-24'	51-58	Enertia ECO	48-8M0127045	48-8M0127044
15.25"	19	3	Steel	4100-4800	22-24'	51-58	Mirage Plus**	48-13700A46	48-13701A46
14.2"	18	3	Steel	4400-5100	22-25'	48-55	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	4400-5100	22-25'	48-55	Enertia ECO	48-8M0127043	48-8M0127042
14.62"	18	4	Steel	4400-5100	22-25'	48-55	Revolution 4	48-8M0137924	48-8M0137925
14.5"	17	3	Steel	4800-5600	23-25'	44-51	Enertia**	48-898994A46	48-898994A46
16.00"	17	3	Steel	4800-5600	23-25'	44-51	Enertia ECO	48-8M0127041	48-8M0127040
15.5"	17	3	Steel	4800-5600	23-25'	44-51	Mirage Plus**	48-18278A46	48-90159A46
14.62"	17	4	Steel	4800-5600	23-25'	44-51	Revolution 4	48-8M0127029	48-8M0127028

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit

PROPELLERS

WOT RPM: 4800-5600 * Recommended Transom Height 20", 25", 30" * Right Hand Rotation (Left Hand Available) * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
13.8"	21	3	Steel	3100-3800	20-22'	48-58	Enertia**	48-899002A46	48-899003A46
16.00"	21	3	Steel	3100-3800	20-22'	48-58	Enertia ECO	48-8M0127049	48-8M0127048
14.62"	21	4	Steel	3100-3800	20-22'	48-58	Revolution 4	48-8M0127035	48-8M0127034
14.75"	21	3	Steel	3100-3800	20-22'	48-58	Mirage Plus**	48-13702A46	48-13703A46
13.8"	20	3	Steel	3300-4100	20-23'	45-55	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	3300-4100	20-23'	45-55	Enertia ECO	48-8M0127047	48-8M0127046
14.62"	20	4	Steel	3300-4100	20-23'	45-55	Revolution 4	48-8M0127033	48-8M0127032
14.0"	19	3	Steel	3500-4500	21-24'	42-52	Enertia**	48-898998A46	48-898999A46
14.62"	19	4	Steel	3500-4500	21-24'	42-52	Revolution 4	48-8M0127031	48-8M0127030
16.00"	19	3	Steel	3500-4500	21-24'	42-52	Enertia ECO	48-8M0127045	48-8M0127044
15.25"	19	3	Steel	3500-4500	21-24'	42-52	Mirage Plus**	48-13700A46	48-13701A46
14.2"	18	3	Steel	3700-5000	21-25'	38-49	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	3700-5000	21-25'	38-49	Enertia ECO	48-8M0127043	48-8M0127042
14.62"	18	4	Steel	3700-5000	21-25'	38-49	Revolution 4	48-8M0137924	48-8M0137925
14.5"	17	3	Steel	4000-5500	22-25'	35-46	Enertia**	48-898994A46	48-898994A46
16.00"	17	3	Steel	4000-5500	22-25'	35-46	Enertia ECO	48-8M0127041	48-8M0127040
15.5"	17	3	Steel	4000-5500	22-25'	35-46	Mirage Plus**	48-18278A46	48-90159A46
14.62"	17	4	Steel	4000-5500	22-25'	35-46	Revolution 4	48-8M0127029	48-8M0127028
14.7"	16	3	Steel	4300-6100	22-26'	32-43	Enertia**	48-898992A46	N/A
15.0"	15	3	Steel	4700-7000	23-27'	28-40	Enertia**	48-898990A46	48-898991A46
15.75"	15	3	Steel	4700-7000	23-27'	28-40	Mirage Plus**	48-19838A46	48-19841A46
14.62"	15	4	Steel	4700-7000	23-27'	28-40	Revolution 4	48-8M0127027	48-8M0127026
15.3"	14	3	Steel	5100-8000	24-28'	25-37	Enertia**	48-898988A46	N/A
15.6"	13	3	Steel	5800-9700	25-30'	21-33	Enertia**	48-8M0070074	48-8M0070076
16.00"	13	3	Steel	5800-9700	25-30'	21-33	Mirage Plus**	48-826072A46	N/A
16.0"	11	3	Steel	7000+	27'+	14-26	Enertia**	48-8M0070079	48-8M0070077

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit



FURY 4

Mercury's high performance tournament load bass propeller.

Designed for unmatched performance for the angler running heavily weighted 20 - 22' bass boats.



Bravo I

The world's best-selling high-performance propeller.

Ideal fit for high-speed, high-drive-height outboard and Bravo One sterndrive applications.

PROPELLERS

WOT RPM: 4800-5600 * Recommended Transom Height 20", 25", 30" * Right Hand Rotation (Left Hand Available) * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
13.5"	22	3	Steel	3300-4100	20-23'	50-61	Enertia**	48-899202A46	N/A
16.00"	22	3	Steel	3300-4100	20-23'	50-61	Enertia ECO	48-8M0127051	48-8M0127050
13.8"	21	3	Steel	3400-4300	20-23'	48-58	Enertia**	48-899002A46	48-899003A46
16.00"	21	3	Steel	3400-4300	20-23'	48-58	Enertia ECO	48-8M0127049	48-8M0127048
14.62"	21	4	Steel	3400-4300	20-23'	48-58	Revolution 4	48-8M0127035	48-8M0127034
14.75"	21	3	Steel	3400-4300	20-23'	48-58	Mirage Plus**	48-13702A46	48-13703A46
13.8"	20	3	Steel	3700-4600	21-24'	45-55	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	3700-4600	21-24'	45-55	Enertia ECO	48-8M0127047	48-8M0127046
14.62"	20	4	Steel	3700-4600	21-24'	45-55	Revolution 4	48-8M0127033	48-8M0127032
14.0"	19	3	Steel	3900-5000	22-25'	42-52	Enertia**	48-898998A46	48-898999A46
14.62"	19	4	Steel	3900-5000	22-25'	42-52	Revolution 4	48-8M0127031	48-8M0127030
16.00"	19	3	Steel	3900-5000	22-25'	42-52	Enertia ECO	48-8M0127045	48-8M0127044
15.25"	19	3	Steel	3900-5000	22-25'	42-52	Mirage Plus**	48-13700A46	48-13701A46
14.2"	18	3	Steel	4200-5500	22-25'	38-49	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	4200-5500	22-25'	38-49	Enertia ECO	48-8M0127043	48-8M0127042
14.62"	18	4	Steel	4200-5500	22-25'	38-49	Revolution 4	48-8M0137924	48-8M0137925
14.5"	17	3	Steel	4500-6100	23-26'	35-46	Enertia**	48-898994A46	48-898994A46
16.00"	17	3	Steel	4500-6100	23-26'	35-46	Enertia ECO	48-8M0127041	48-8M0127040
15.5"	17	3	Steel	4500-6100	23-26'	35-46	Mirage Plus**	48-18278A46	48-90159A46
14.62"	17	4	Steel	4500-6100	23-26'	35-46	Revolution 4	48-8M0127029	48-8M0127028
14.7"	16	3	Steel	4800-6700	23-27'	32-43	Enertia**	48-898992A46	N/A
15.0"	15	3	Steel	5200-7800	24-28'	28-40	Enertia**	48-898990A46	48-898991A46
15.75"	15	3	Steel	5200-7800	24-28'	28-40	Mirage Plus**	48-19838A46	48-19841A46
14.62"	15	4	Steel	5200-7800	24-28'	28-40	Revolution 4	48-8M0127027	48-8M0127026
15.3"	14	3	Steel	5700-8900	25-29'	25-37	Enertia**	48-898988A46	N/A
15.6"	13	3	Steel	6500-10800	26-31'	21-33	Enertia**	48-8M0070074	48-8M0070076
16.00"	13	3	Steel	6500-10800	26-31'	21-33	Mirage Plus**	48-826072A46	N/A
16.0"	11	3	Steel	8000+	28'+	14-26	Enertia**	48-8M0070079	48-8M0070077

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit



High Five

Five-blade stainless steel design offers ultimate hole shot and handling.

Perfect propeller for supreme tow sport performance.



Mirage Plus

Best-selling high-horsepower propeller in the world.

Large diameter design works well across a wide range of applications.

PROPELLERS

WOT RPM: 4800-5600 * Recommended Transom Height 20", 25", 30" * Right Hand Rotation (Left Hand Available) * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
13.5"	22	3	Steel	3900-4900	22-24'	50-61	Enertia**	48-899202A46	N/A
16.00"	22	3	Steel	3900-4900	22-24'	50-61	Enertia ECO	48-8M0127051	48-8M0127050
13.8"	21	3	Steel	4100-5100	22-25'	48-58	Enertia**	48-899002A46	48-899003A46
16.00"	21	3	Steel	4100-5100	22-25'	48-58	Enertia ECO	48-8M0127049	48-8M0127048
14.62"	21	4	Steel	4100-5100	22-25'	48-58	Revolution 4	48-8M0127035	48-8M0127034
14.75"	21	3	Steel	4100-5100	22-25'	48-58	Mirage Plus**	48-13702A46	48-13703A46
13.8"	20	3	Steel	4400-5500	22-25'	45-55	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	4400-5500	22-25'	45-55	Enertia ECO	48-8M0127047	48-8M0127046
14.62"	20	4	Steel	4400-5500	22-25'	45-55	Revolution 4	48-8M0127033	48-8M0127032
14.0"	19	3	Steel	4700-5900	23-26'	42-52	Enertia**	48-898998A46	48-898999A46
14.62"	19	4	Steel	4700-5900	23-26'	42-52	Revolution 4	48-8M0127031	48-8M0127030
16.00"	19	3	Steel	4700-5900	23-26'	42-52	Enertia ECO	48-8M0127045	48-8M0127044
15.25"	19	3	Steel	4700-5900	23-26'	42-52	Mirage Plus**	48-13700A46	48-13701A46
14.2"	18	3	Steel	5000-6600	24-27'	38-49	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	5000-6600	24-27'	38-49	Enertia ECO	48-8M0127043	48-8M0127042
14.62"	18	4	Steel	5000-6600	24-27'	38-49	Revolution 4	48-8M0137924	48-8M0137925
14.5"	17	3	Steel	5400-7300	24-28'	35-46	Enertia**	48-898994A46	48-898994A46
16.00"	17	3	Steel	5400-7300	24-28'	35-46	Enertia ECO	48-8M0127041	48-8M0127040
15.5"	17	3	Steel	5400-7300	24-28'	35-46	Mirage Plus**	48-18278A46	48-90159A46
14.62"	17	4	Steel	5400-7300	24-28'	35-46	Revolution 4	48-8M0127029	48-8M0127028
14.7"	16	3	Steel	5800-8100	25-29'	32-43	Enertia**	48-898992A46	N/A
15.0"	15	3	Steel	6300-9400	25-30'	28-40	Enertia**	48-898990A46	48-898991A46
15.75"	15	3	Steel	6300-9400	25-30'	28-40	Mirage Plus**	48-19838A46	48-19841A46
14.62"	15	4	Steel	6300-9400	25-30'	28-40	Revolution 4	48-8M0127027	48-8M0127026
15.3"	14	3	Steel	6900-10700	26-31'	25-37	Enertia**	48-898988A46	N/A
15.6"	13	3	Steel	7800-13000	27-32'	21-33	Enertia**	48-8M0070074	48-8M0070076
16.00"	13	3	Steel	7800-13000	27-32'	21-33	Mirage Plus**	48-826072A46	N/A
16.0"	11	3	Steel	9000+	29'+	14-26	Enertia**	48-8M0070079	48-8M0070077

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit



Spitfire

Mercury's state-of-the-art aluminum propeller provides three-blade speed with four-blade holding and acceleration.



Tempest Plus

Designed to make big boats go fast. Higher rake and bigger cup provide better handling and lift on big V6 outboard-powered boats.

PROPELLERS

WOT RPM: 5400-6000 * Recommended Transom Height 20", 25" * Right Hand Rotation * Gear Ratio 1.85:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.00"	27	3	Steel	Up to 2000	Up to 18'	68-77	Fury**	48-8M8023180	N/A
13.75"	27	4	Steel	Up to 2000	Up to 18'	68-77	Trophy Plus**	48-825946A46	N/A
14.62"	27	3	Steel	Up to 2000	Up to 18'	68-77	Tempest Plus**	48-825868A47	N/A
14.00"	26	3	Steel	Up to 2100	Up to 18'	65-74	Fury	48-8M0125098	N/A
13.75"	26	4	Steel	Up to 2100	Up to 18'	65-74	Trophy Plus**	48-825944A47	N/A
14.62"	26	3	Steel	Up to 2100	Up to 18'	65-74	Tempest Plus**	48-825874A47	N/A
14.00"	25	3	Steel	1900-2200	16-19'	62-71	Fury	48-8M0125097	N/A
13.75"	25	4	Steel	1900-2200	16-19'	62-71	Trophy Plus**	48-825942A47	N/A
14.62"	25	3	Steel	1900-2200	16-19'	62-71	Tempest Plus**	48-825866A47	N/A
14.00"	24	3	Steel	2000-2300	17-19'	60-67	Fury	48-8M0125096	N/A
13.75"	24	4	Steel	2000-2300	17-19'	60-67	Trophy Plus**	48-825940A47	N/A
14.62"	24	3	Steel	2000-2300	17-19'	60-67	Tempest Plus**	48-825872A47	N/A
14.00"	23	3	Steel	2000-2300	17-19'	57-64	Fury	48-8M0125095	N/A
13.75"	23	4	Steel	2200-2500	17-19'	57-64	Trophy Plus**	48-825938A47	N/A
14.62"	23	3	Steel	2200-2500	17-19'	57-64	Tempest Plus**	48-825864A47	N/A
13.25"	23	5	Steel	2200-2500	17-19'	57-64	Hi-Five**	48-815762A46	N/A
13.5"	22	3	Steel	2300-2600	17-20'	54-61	Enertia**	48-899202A46	N/A
13.75"	21	4	Steel	2400-2800	18-20'	51-58	Trophy Plus**	48-825934A47	N/A
14.62"	21	3	Steel	2400-2800	18-20'	51-58	Tempest Plus**	48-825862A47	N/A
13.62"	21	3	Steel	2400-2800	18-20'	51-58	Enertia**	48-899002A46	N/A
13.25"	21	5	Steel	2400-2800	18-20'	51-58	Hi-Five**	48-815760A46	N/A
13.75"	21	3	Steel	2400-2800	18-20'	51-58	Vengeance**	48-16318A46	N/A
13.75"	20	3	Steel	2500-3000	18-20'	48-56	Enertia**	48-899000A46	N/A
14.62"	19	3	Steel	2700-3200	18-21'	45-53	Tempest Plus**	48-825860A47	N/A
14.0"	19	3	Steel	2700-3200	18-21'	45-53	Enertia**	48-898998A46	N/A
13.25"	19	5	Steel	2700-3200	18-21'	45-53	Hi-Five**	48-815758A46	N/A
14"	19	3	Steel	2700-3200	18-21'	45-53	Vengeance**	48-16316A46	N/A

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit



Black Max

World's best selling aluminum propeller.

Perfect combination of performance, durability and value.



Vengeance Propeller

All-purpose stainless steel propeller offers improved performance and durability over aluminum propellers.

PROPELLERS

WOT RPM: 5200-6000 * Recommended Transom Height 20", 25", 30" * Right Hand Rotation (Left Hand Available) * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
13.5"	22	3	Steel	3000-3700	19-22'	55-65	Enertia**	48-899202A46	N/A
16.00"	22	3	Steel	3000-3700	19-22'	55-65	Enertia ECO	48-8M0127051	48-8M0127050
14.62"	21	3	Steel	3200-3900	20-23'	52-62	Tempest Plus**	48-825862A47	N/A
13.8"	21	3	Steel	3200-3900	20-23'	52-62	Enertia**	48-899002A46	48-899003A46
16.00"	21	3	Steel	3200-3900	20-23'	52-62	Enertia ECO	48-8M0127049	48-8M0127048
13.25"	21	5	Steel	3200-3900	20-23'	52-62	HighFive**	48-815760A46	N/A
14.62"	21	4	Steel	3200-3900	20-23'	52-62	Revolution 4	48-8M0127035	48-8M0127034
13.8"	20	3	Steel	3400-4200	20-23'	49-59	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	3400-4200	20-23'	49-59	Enertia ECO	48-8M0127047	48-8M0127046
14.62"	20	4	Steel	3400-4200	20-23'	49-59	Revolution 4	48-8M0127033	48-8M0127032
14.62"	19	3	Steel	3600-4500	21-24'	46-56	Tempest Plus**	48-825860A47	N/A
14.0"	19	3	Steel	3600-4500	21-24'	46-56	Enertia**	48-898998A46	48-898999A46
13.25"	19	5	Steel	3600-4500	21-24'	46-56	HighFive**	48-815758A46	N/A
14.62"	19	4	Steel	3600-4500	21-24'	46-56	Revolution 4	48-8M0127031	48-8M0127030
16.00"	19	3	Steel	3600-4500	21-24'	46-56	Enertia ECO	48-8M0127045	48-8M0127044
15.25"	19	3	Steel	3600-4500	21-24'	46-56	Mirage Plus**	48-13700A46	48-13701A46
14.2"	18	3	Steel	3800-4800	21-24'	43-53	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	3800-4800	21-24'	43-53	Enertia ECO	48-8M0127043	48-8M0127042
14.62"	18	4	Steel	3800-4800	21-24'	43-53	Revolution 4	48-8M0137924	48-8M0137925
14.5"	17	3	Steel	4100-5200	22-25'	40-50	Enertia**	48-898994A46	48-898994A46
16.00"	17	3	Steel	4100-5200	22-25'	40-50	Enertia ECO	48-8M0127041	48-8M0127040
15.5"	17	3	Steel	4100-5200	22-25'	40-50	Mirage Plus**	48-18278A46	48-90159A46
13.5"	17	5	Steel	4100-5200	22-25'	40-50	HighFive**	48-821154A46	N/A
14.62"	17	4	Steel	4100-5200	22-25'	40-50	Revolution 4	48-8M0127029	48-8M0127028
14.7"	16	3	Steel	4500-5900	23-26'	36-46	Enertia**	48-898992A46	N/A
15.0"	15	3	Steel	4800-6500	23-27'	33-43	Enertia**	48-898990A46	48-898991A46
15.75"	15	3	Steel	4800-6500	23-27'	33-43	Mirage Plus**	48-19838A46	48-19841A46
14.62"	15	4	Steel	4800-6500	23-27'	33-43	Revolution 4	48-8M0127027	48-8M0127026
15.3"	14	3	Steel	5200-7500	24-28'	29-40	Enertia**	48-898988A46	N/A
15.6"	13	3	Steel	5900-8900	25-29'	25-36	Enertia**	48-8M0070074	48-8M0070076
16.00"	13	3	Steel	5900-8900	25-29'	25-36	Mirage Plus**	48-826072A46	N/A
16.0"	11	3	Steel	7000+	27'+	18-29	Enertia**	48-8M0070079	48-8M0070077

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit



PROPELLERS

WOT RPM: 5200-6000 * Recommended Transom Height 20", 25", 30" * Right Hand Rotation (Left Hand Available) * Gear Ratio 1.75:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
13.5"	22	3	Steel	3600-4400	21-23'	55-65	Enertia**	48-899202A46	N/A
16.00"	22	3	Steel	3600-4400	21-23'	55-65	Enertia ECO	48-8M0127051	48-8M0127050
14.62"	21	3	Steel	3800-4700	21-24'	52-62	Tempest Plus**	48-825862A47	N/A
13.8"	21	3	Steel	3800-4700	21-24'	52-62	Enertia**	48-899002A46	48-899003A46
16.00"	21	3	Steel	3800-4700	21-24'	52-62	Enertia ECO	48-8M0127049	48-8M0127048
13.25"	21	5	Steel	3800-4700	21-24'	52-62	HighFive**	48-815760A46	N/A
14.62"	21	4	Steel	3800-4700	21-24'	52-62	Revolution 4	48-8M0127035	48-8M0127034
14.75"	21	3	Steel	3800-4700	21-24'	52-62	Mirage Plus**	48-13702A46	48-13703A46
13.8"	20	3	Steel	4100-5000	22-25'	49-59	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	4100-5000	22-25'	49-59	Enertia ECO	48-8M0127047	48-8M0127046
14.62"	20	4	Steel	4100-5000	22-25'	49-59	Revolution 4	48-8M0127033	48-8M0127032
14.62"	19	3	Steel	4300-5400	22-25'	46-56	Tempest Plus**	48-825860A47	N/A
14.0"	19	3	Steel	4300-5400	22-25'	46-56	Enertia**	48-898998A46	48-898999A46
13.25"	19	5	Steel	4300-5400	22-25'	46-56	HighFive**	48-815758A46	N/A
14.62"	19	4	Steel	4300-5400	22-25'	46-56	Revolution 4	48-8M0127031	48-8M0127030
16.00"	19	3	Steel	4300-5400	22-25'	46-56	Enertia ECO	48-8M0127045	48-8M0127044
15.25"	19	3	Steel	4300-5400	22-25'	46-56	Mirage Plus**	48-13700A46	48-13701A46
14.2"	18	3	Steel	4600-5800	23-26'	43-53	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	4600-5800	23-26'	43-53	Enertia ECO	48-8M0127043	48-8M0127042
14.62"	18	4	Steel	4600-5800	23-26'	43-53	Revolution 4	48-8M0137924	48-8M0137925
14.5"	17	3	Steel	4900-6300	23-26'	40-50	Enertia**	48-898994A46	48-898994A46
16.00"	17	3	Steel	4900-6300	23-26'	40-50	Enertia ECO	48-8M0127041	48-8M0127040
15.5"	17	3	Steel	4900-6300	23-26'	40-50	Mirage Plus**	48-18278A46	48-90159A46
13.5"	17	5	Steel	4900-6300	23-26'	40-50	HighFive**	48-821154A46	N/A
14.62"	17	4	Steel	4900-6300	23-26'	40-50	Revolution 4	48-8M0127029	48-8M0127028
14.7"	16	3	Steel	5400-7100	24-27'	36-46	Enertia**	48-898992A46	N/A
15.0"	15	3	Steel	5800-7800	25-28'	33-43	Enertia**	48-898990A46	48-898991A46
15.75"	15	3	Steel	5800-7800	25-28'	33-43	Mirage Plus**	48-19838A46	48-19841A46
14.62"	15	4	Steel	5800-7800	25-28'	33-43	Revolution 4	48-8M0127027	48-8M0127026
15.3"	14	3	Steel	6300-9000	25-29'	29-40	Enertia**	48-898988A46	N/A
15.6"	13	3	Steel	7100-10700	26-31'	25-36	Enertia**	48-8M0070074	48-8M0070076
16.00"	13	3	Steel	7100-10700	26-31'	25-36	Mirage Plus**	48-826072A46	N/A
16.0"	11	3	Steel	8000+	29'+	18-29	Enertia**	48-8M0070079	48-8M0070077

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit

PROPELLERS

WOT RPM: 5200-6000 * Recommended Transom Height 20", 25", 30" * Right Hand Rotation (Left Hand Available) * Gear Ratio 1.85:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.62"	23	3	Steel	3100-3700	20-22'	55-64	Tempest Plus**	48-825864A47	N/A
16.00"	23	3	Steel	3100-3700	20-22'	55-64	Enertia ECO	48-8M0127053	48-8M0127052
13.25"	23	5	Steel	3100-3700	20-22'	55-64	HighFive**	48-815762A46	N/A
14.62"	23	4	Steel	3100-3700	20-22'	55-64	Revolution 4	48-8M0127037	48-8M0127036
14.62"	23	3	Steel	3100-3700	20-22'	55-64	Mirage Plus**	48-13704A46	48-13705A46
13.5"	22	3	Steel	3300-3900	20-23'	52-61	Enertia**	48-899202A46	N/A
16.00"	22	3	Steel	3300-3900	20-23'	52-61	Enertia ECO	48-8M0127051	48-8M0127050
14.62"	21	3	Steel	3400-4200	20-23'	49-58	Tempest Plus**	48-825862A47	N/A
13.8"	21	3	Steel	3400-4200	20-23'	49-58	Enertia**	48-899002A46	48-899003A46
16.00"	21	3	Steel	3400-4200	20-23'	49-58	Enertia ECO	48-8M0127049	48-8M0127048
13.25"	21	5	Steel	3400-4200	20-23'	49-58	HighFive**	48-815760A46	N/A
14.62"	21	4	Steel	3400-4200	20-23'	49-58	Revolution 4	48-8M0127035	48-8M0127034
14.75"	21	3	Steel	3400-4200	20-23'	49-58	Mirage Plus**	48-13702A46	48-13703A46
13.8"	20	3	Steel	3600-4500	21-24'	46-56	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	3600-4500	21-24'	46-56	Enertia ECO	48-8M0127047	48-8M0127046
14.62"	20	4	Steel	3600-4500	21-24'	46-56	Revolution 4	48-8M0127033	48-8M0127032
14.62"	19	3	Steel	3800-4800	21-24'	43-53	Tempest Plus**	48-825860A47	N/A
14.0"	19	3	Steel	3800-4800	21-24'	43-53	Enertia**	48-898998A46	48-898999A46
13.25"	19	5	Steel	3800-4800	21-24'	43-53	HighFive**	48-815758A46	N/A
14.62"	19	4	Steel	3800-4800	21-24'	43-53	Revolution 4	48-8M0127031	48-8M0127030
16.00"	19	3	Steel	3800-4800	21-24'	43-53	Enertia ECO	48-8M0127045	48-8M0127044
15.25"	19	3	Steel	3800-4800	21-24'	43-53	Mirage Plus**	48-13700A46	48-13701A46
14.2"	18	3	Steel	4100-5200	22-25'	40-50	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	4100-5200	22-25'	40-50	Enertia ECO	48-8M0127043	48-8M0127042
14.62"	18	4	Steel	4100-5200	22-25'	40-50	Revolution 4	48-8M0137924	48-8M0137925
14.5"	17	3	Steel	4400-5700	22-26'	37-47	Enertia**	48-898994A46	48-898994A46
16.00"	17	3	Steel	4400-5700	22-26'	37-47	Enertia ECO	48-8M0127041	48-8M0127040
15.5"	17	3	Steel	4400-5700	22-26'	37-47	Mirage Plus**	48-18278A46	48-90159A46
13.5"	17	5	Steel	4400-5700	22-26'	37-47	HighFive**	48-821154A46	N/A
14.62"	17	4	Steel	4400-5700	22-26'	37-47	Revolution 4	48-8M0127029	48-8M0127028
14.7"	16	3	Steel	4700-6500	23-27'	33-44	Enertia**	48-898992A46	N/A
15.0"	15	3	Steel	5200-7200	24-28'	30-40	Enertia**	48-898990A46	48-898991A46
15.75"	15	3	Steel	5200-7200	24-28'	30-40	Mirage Plus**	48-19838A46	48-19841A46
14.62"	15	4	Steel	5200-7200	24-28'	30-40	Revolution 4	48-8M0127027	48-8M0127026
15.3"	14	3	Steel	5700-8500	25-29'	26-37	Enertia**	48-898988A46	N/A
15.6"	13	3	Steel	6300-9800	25-30'	23-34	Enertia**	48-8M0070074	48-8M0070076
16.00"	13	3	Steel	6300-9800	25-30'	23-34	Mirage Plus**	48-826072A46	N/A
16.0"	11	3	Steel	7500+	28'+	15-27	Enertia**	48-8M0070079	48-8M0070077

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit



PROPELLERS

WOT RPM: 5200-6000 * Recommended Transom Height 20", 25", 30" * Right Hand Rotation (Left Hand Available) * Gear Ratio 1.85:1

Diameter (inches)	Pitch (inches)	Blades	Material	Approx. Gross Boat Wgt. (lbs.)	Approx. Boat Length (ft.)	Speed Range (mph)	Propeller Description	Right Hand Propeller Part Number	Left Hand Propeller Part Number
14.62"	23	3	Steel	3700-4400	21-23'	55-64	Tempest Plus**	48-825864A47	N/A
16.00"	23	3	Steel	3700-4400	21-23'	55-64	Enertia ECO	48-8M0127053	48-8M0127052
13.25"	23	5	Steel	3700-4400	21-23'	55-64	HighFive**	48-815762A46	N/A
14.62"	23	4	Steel	3700-4400	21-23'	55-64	Revolution 4	48-8M0127037	48-8M0127036
14.62"	23	3	Steel	3700-4400	21-23'	55-64	Mirage Plus**	48-13704A46	48-13705A46
13.5"	22	3	Steel	3900-4700	22-24'	52-61	Enertia**	48-899202A46	N/A
16.00"	22	3	Steel	3900-4700	22-24'	52-61	Enertia ECO	48-8M0127051	48-8M0127050
14.62"	21	3	Steel	4100-5000	22-25'	49-58	Tempest Plus**	48-825862A47	N/A
13.8"	21	3	Steel	4100-5000	22-25'	49-58	Enertia**	48-899002A46	48-899003A46
16.00"	21	3	Steel	4100-5000	22-25'	49-58	Enertia ECO	48-8M0127049	48-8M0127048
13.25"	21	5	Steel	4100-5000	22-25'	49-58	HighFive**	48-815760A46	N/A
14.62"	21	4	Steel	4100-5000	22-25'	49-58	Revolution 4	48-8M0127035	48-8M0127034
14.75"	21	3	Steel	4100-5000	22-25'	49-58	Mirage Plus**	48-13702A46	48-13703A46
13.8"	20	3	Steel	4300-5400	22-25'	46-56	Enertia**	48-899000A46	N/A
16.00"	20	3	Steel	4300-5400	22-25'	46-56	Enertia ECO	48-8M0127047	48-8M0127046
14.62"	20	4	Steel	4300-5400	22-25'	46-56	Revolution 4	48-8M0127033	48-8M0127032
14.62"	19	3	Steel	4600-5800	23-26'	43-53	Tempest Plus**	48-825860A47	N/A
14.0"	19	3	Steel	4600-5800	23-26'	43-53	Enertia**	48-898998A46	48-898999A46
13.25"	19	5	Steel	4600-5800	23-26'	43-53	HighFive**	48-815758A46	N/A
14.62"	19	4	Steel	4600-5800	23-26'	43-53	Revolution 4	48-8M0127031	48-8M0127030
16.00"	19	3	Steel	4600-5800	23-26'	43-53	Enertia ECO	48-8M0127045	48-8M0127044
15.25"	19	3	Steel	4600-5800	23-26'	43-53	Mirage Plus**	48-13700A46	48-13701A46
14.2"	18	3	Steel	4900-6300	23-26'	40-50	Enertia**	48-898996A46	N/A
16.00"	18	3	Steel	4900-6300	23-26'	40-50	Enertia ECO	48-8M0127043	48-8M0127042
14.62"	18	4	Steel	4900-6300	23-26'	40-50	Revolution 4	48-8M0137924	48-8M0137925
14.5"	17	3	Steel	5200-6900	24-27'	37-47	Enertia**	48-898994A46	48-898994A46
16.00"	17	3	Steel	5200-6900	24-27'	37-47	Enertia ECO	48-8M0127041	48-8M0127040
15.5"	17	3	Steel	5200-6900	24-27'	37-47	Mirage Plus**	48-18278A46	48-90159A46
13.5"	17	5	Steel	5200-6900	24-27'	37-47	HighFive**	48-821154A46	N/A
14.62"	17	4	Steel	5200-6900	24-27'	37-47	Revolution 4	48-8M0127029	48-8M0127028
14.7"	16	3	Steel	5600-7800	24-28'	33-44	Enertia**	48-898992A46	N/A
15.0"	15	3	Steel	6300-8700	25-29'	30-40	Enertia**	48-898990A46	48-898991A46
15.75"	15	3	Steel	6300-8700	25-29'	30-40	Mirage Plus**	48-19838A46	48-19841A46
14.62"	15	4	Steel	6300-8700	25-29'	30-40	Revolution 4	48-8M0127027	48-8M0127026
15.3"	14	3	Steel	6900-10200	26-30'	26-37	Enertia**	48-898988A46	N/A
15.6"	13	3	Steel	7500-11700	27-32'	23-34	Enertia**	48-8M0070074	48-8M0070076
16.00"	13	3	Steel	7500-11700	27-32'	23-34	Mirage Plus**	48-826072A46	N/A
16.0"	11	3	Steel	8500+	30'+	15-27	Enertia	48-8M0070079	48-8M0070077

**must use SSR HD (8M0101601) or Flo-Torq II solid (840389K06) hub kit