



NAUTIC GREASE

High Performance Multipurpose Marine Grease

NLGI 2 - Extreme Pressure

Technosynthese® - Calcium - PTFE

TYPE OF USE

High performance multipurpose water resistant grease with Extreme Pressure properties, developed to lubricate and protect all mechanical parts against corrosion and wear in sea salted environments and other adverse conditions common to marine usage.

Ideal applications include open gears, ball bearings, roller bearings, plain bearings, pivot pins, anchor cables, and hoist line.

Operating temperature for long-term lubrication: from -30°C / -22°F to +120°C / +248°F.

PERFORMANCE

High quality Technosynthese® grease formulated with Calcium soap, Extreme Pressure, anti-wear, anti-corrosion and anti-oxidation additives.

Contains PTFE (Polytétrafluoroéthylène) to improve lubricity and to offer high compatibility with plastics and elastomers.

Advantages of Motul Nautic Grease :

- Insoluble in water
- High level of adherence on surfaces
- High anti-oxidation and anti-corrosion protection in salt water environments
- High anti-wear Extreme Pressure and thermal resistance properties
- High durability for less grease consumption

PROPERTIES

Color	Visual	Blue
Consistency grade	DIN 51 818	NLGI 2
Soap	Type	Calcium
Base oil viscosity at 40°C	DIN 51 562	800 mm ² /s
Base oil viscosity at 100°C	DIN 51 562	68 mm ² /s
Drop Point	ASTM D 2265	150°C
Penetrability - 60 cycles	ASTM D 217	265 / 295 x10 ⁻¹ mm
Four ball test - welding load	DIN 51 350 T4	4000 N
FAG FE-9 test	DIN 51 821	F50 > 100 hr à 120°C (248°F)
SKF EMCOR Test	ASTM D 6138	2 / 1
Copper corrosion test	ASTM D 4048	1 / 100
Water Washout	DIN 51 807 T1	0 / 90

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel: 33 1 48 11 70 00 – Fax: 33 1 48 33 28 79. Web Site: www.motul.com